

Amendments to the Claims:

The listing of the claims will replace all prior versions and listings of the claims in this application.

Listing of the claims:

1.(Currently Amended) A control valve of a hydraulic brake booster for use in a brake system, said brake booster having a housing with a first bore therein for retaining a power piston, a second bore therein for retaining the control valve and an actuation chamber, said second bore being connected to a source of pressurized fluid, a reservoir and the actuation chamber, said control valve being responsive to an input force from an actuation arrangement for controlling communicating of pressurized fluid available from said source to said actuation chamber that acts on the power piston to effect a brake application and on termination of said input force for controlling communicating of the pressurized fluid present in said actuation chamber to said reservoir; said control valve being characterized by a first cylindrical body located in said second bore, said first cylindrical body having a first stepped axial bore that extends from a first end to a second end, said first stepped bore including a first diameter section adjacent said first end that is separated from a second diameter section by an orifice and a shoulder that separates said second diameter section from a third diameter section adjacent said second end; said first diameter section being connected to said source of pressurized fluid while a first radial bore in said first cylindrical body connects said second diameter section with said actuation chamber and a second radial bore in said first cylindrical body connects said third diameter with said reservoir; a ball located in said first diameter section of said first cylindrical body and a first spring for urging said ball toward a seat adjacent said orifice to define a supply chamber for pressurized fluid within said second bore; a shuttle member that is retained in said second diameter section and having a stem on a first end thereof that is located near said orifice and an annular projection on a second end thereof that

13

extends into said third diameter section of said first cylindrical body; ~~an~~ actuation ~~a power~~ piston retained in said second bore having an annular flange on a first end thereof that is located in said third diameter section of said first cylindrical body and a second end thereof that extends into said actuation chamber, ~~said~~ a second cylindrical body located in said second bore that has a second stepped axial bore that extends from said first end to said second end; a second spring that is located in said first stepped axial bore for urging said second end of said shuttle member thereon toward a first stop within said second bore to define a position of rest for said shuttle member; and a third spring located between said second end of said shuttle member and said first end of said ~~power~~ actuation piston for urging said annular flange toward a second stop to define a position of rest for said ~~power~~ actuation piston where said actuation chamber may freely communicate with said reservoir by way of said second stepped axial bore and said third diameter section and second radial bore in said first cylindrical body, said input force from said actuation arrangement on being applied to said second end of said ~~power~~ actuation piston and after overcoming the force said third spring ~~moving~~ moves said annular flange into engagement with said second end of said shuttle member to terminate communication to said reservoir through said second axial bore and thereafter overcoming the force of said second spring ~~to move~~ moving said stem into engagement with said ball and after thereafter overcoming the force of said first spring moving said ball off said seat to allow metered pressurized fluid to be communicated to said actuation chamber by way of said orifice, second diameter bore and said first radial bore to effect a brake application and on said input force being removed from said second end of said ~~second cylindrical member~~ actuation piston said first spring moving said ball into engagement with said seat to ~~termination~~ terminate communication of pressurized fluid through said orifice while said third spring moves said flange away from said second end of said shuttle member to meter flow of pressurized fluid second present in said actuation chamber to said reservoir by way of said

R75401Am

09/22/2005

14

second stepped axial bore in said ~~second cylindrical member~~ actuation piston, said third diameter and second radial bore in said first cylindrical member.

2.(Currently Amended) The control valve as recited in claim 1 wherein said metered pressurized fluid flow through said orifice increases in a substantially linear function during movement of said shuttle member by said input force applied to said ~~second cylindrical member~~ actuation piston.

3.(Currently Amended) The control valve as recited in claim 2 wherein said stem of said shuttle valve member is characterized by a linear diameter surface that extends a first distance from said first end to a transition point and thereafter a conical diameter surface such that after the transition point passes through the orifice the space relationship between the conical diameter surface and the orifice creates said increases in the flow of pressurized fluid being supplied to said actuation chamber.

4.(Original) The control valve as recited in claim 3 wherein said shuttle member is characterized by an annular rib located adjacent said second end, said annular rib engaging said shoulder on said first cylindrical member to limit the movement of said stem into said orifice and correspondingly the communication of pressurized fluid to said actuation chamber.

5.(Currently Amended) The control valve as recited in claim 4 wherein said annular projection of said second end of said shuttle member is characterized by ~~an axial projection having a conical entry surface~~ that transitions into a ~~cylinder~~ cylindrical surface, said annular flange on said ~~power~~ actuation piston being aligned with said conical entry surface to provide communication path between said second stepped axial bore and said third diameter of said first cylindrical body such that metered pressurized fluid flows from said actuation chamber to said reservoir.

6.(Currently Amended) The control valve as recited in claim 5 further characterized in that said annular flange engages said ~~cylinder~~ cylindrical surface to seal said second stepped axial bore from said third diameter on movement of said ~~power~~ actuation piston by said input force.

R75401Am

09/22/2005

15

7. (Currently Amended) The control valve as recited in claim 5 wherein said first stop is characterized by a sleeve member located in said second stepped axial bore, said sleeve member having a length to set a distance between said conical entry surface and said annular flange to provide for open communication between said second stepped axial bore and said third diameter.

8.(Currently Amended) The control valve as recited in claim 7 wherein ~~said second stop~~ is characterized by an annular spacer ~~fixed~~ located within said second bore to define a second stop, said annular spacer being concentric with said power actuation piston and having a shoulder toward which said third spring urges said annular flange to assist in defining said ~~a~~ flow path to permit open communication between said second stepped axial bore and said third diameter during periods of rest.

9.(Currently Amended) The control valve as recited in claim 8 is further characterized by a second sleeve located within said ~~spacer~~ second cylindrical body with a first end having a second flange thereon that is located between said first annular flange on said actuator piston and said a shoulder on said second cylindrical body thereof and a second end located in a second chamber within said ~~spacer~~ second bore that is connected to a source of pressurized fluid.

10.(Currently Amended) The control valve as recited in claim 9 wherein said second end of second sleeve responds to pressurized fluid by moving within said ~~space~~ second cylindrical body to provide a force to move said first annular flange on said actuator piston and correspondingly said shuttle member to effect a brake application.

11.(Currently Amended) A control valve of a hydraulic brake booster for use in a brake system, said brake booster having a housing with a first bore therein for retaining a power piston, a second bore therein for retaining the control valve and an actuation chamber, said second bore being connected to a source of pressurized fluid, a reservoir and the actuation chamber, said control valve being responsive to an input force from an actuation arrangement for

R75401Am

09/22/2005

16

controlling communicating of pressurized fluid available from said source to said actuation chamber that acts on the power piston to effect a brake application and on termination of said input force for controlling communicating of the pressurized fluid present in said actuation chamber to said reservoir; said control valve being characterized by a shuttle member that is sealingly retained in said second bore and having a stem on a first end that is located near an orifice through which pressurized fluid is communicated to said ~~the~~ actuation chamber as a function of movement of said shuttle member and an annular projection on a second end; a cylindrical body retained in said second bore with a flange on a first end that is located in said second bore and a second end that is connected to said actuation chamber with an axial bore that extends from said first end to said second end; a first return spring for urging said second end of said shuttle member toward a first stop within said second bore to define a position of rest for said shuttle member; and a second return spring located between said shuttle member and said cylindrical body for urging said flange toward a second stop to define a position of rest for said cylindrical body where said actuation chamber is in free communication with said reservoir by way of said axial bore and said second bore, said input force from said actuation arrangement on being applied to said second end of said cylindrical body and after overcoming the force said second return spring moving said flange into engagement with said annular projection of said shuttle member to terminate communication through said axial bore to said reservoir and thereafter overcoming the force of said first return spring moving said stem into said orifice and into engagement with a ball and then after overcoming the force of a valve spring moving said ball off a seat to allow metered pressurized fluid to be communicated to said actuation chamber by way of said orifice to effect a brake application and on said input force being removed from said cylindrical body said valve spring moving said ball into engagement with said seat to ~~termination~~ terminate communication of pressurized fluid through said orifice while said ~~first~~ second return spring moves said flange away from said annular

R75401Am

09/22/2005

17

projection on said shuttle member to meter flow of pressurized fluid ~~second~~ present in said actuation chamber to said reservoir by way of said axial bore such that flow of fluid is always in a same direction from said orifice toward said axial bore to attenuate the introduction of oscillatory forces into the shuttle member that may create noise.

12.(Currently Amended) The control valve as recited in claim 11 wherein said stem of said shuttle valve is characterized by a linear diameter surface that extends a first distance from said first end to a transition point of a conical diameter surface such that after the transition point passes through the orifice a space relationship between the conical diameter surface and the orifice creates an ~~increases~~ increase in the flow of pressurized fluid being supplied to said actuation chamber.

13.(Original) The control valve as recited in claim 12 wherein said shuttle member is further characterized by an annular rib located adjacent said second end, said annular rib engaging a shoulder within said second bore to limit the movement of said stem into said orifice and correspondingly the communication of pressurized fluid to said actuation chamber.

14.(Currently Amended) The control valve as recited in claim 13 wherein said annular projection is characterized by a conical entry surface that transitions into a ~~cylinder~~ cylindrical surface, said flange on said cylindrical body being aligned with said conical entry surface such that a flow path occurs between said axial bore and said reservoir in said position of rest for said cylindrical body and metered pressurized fluid flows from said actuation chamber to said reservoir upon termination of a brake application.

15.(Currently Amended) The control valve as recited in claim 14 further characterized in that said flange engages said ~~cylinder~~ cylindrical surface on said annular projection to seal said axial bore from said reservoir on movement of said cylindrical body by said input force.

R75401Am

09/22/2005